

## ATA2700 Torque Tube

300 ft/lb (406 Nm) Torque  
135 lbs[61.2kg] Balance Capacity

MAX TORQUE: Up to 300 ft/lb (406 Nm)  
BALANCING CAPACITY MAX @ 100 psi: 135 lbs[61.2kg]

- Zero-gravity tool balancing
- Absorbs torque reaction
- Reduces operator fatigue
- Either swivel or fixed tool
- Either fixed or rotational bearing extension

ORDER # EXAMPLE 1: ATA2700\_B\_L175\_M24  
ORDER # EXAMPLE 2: ATA2700\_K175

MODEL #			
ATA2700	X	XXXX	XXX
Optional [Omit if not required]			

RAIL	MODEL #	TROLLEY	TOOL SIZES	MODEL #	TOOL HOLDER	
Knight RAD4110 4" Rail	B		1.75"-2.25" [44.45mm-57.15mm] Adjustable Clamp	K175	 ASA9521	
						MRTA4027
Knight RAD7510 8" Rail	C		1.00"[25.4mm] Dia. Clamp	L100	1.00" - 2.44" (1/16" Increments) FREE ROTATION  ASA9519-x.xx (ASA9519-1.00")	
				1.13"[28.70mm] Dia. Clamp		L113
				1.19"[30.22mm] Dia. Clamp		L119
				1.25"[31.75mm] Dia. Clamp		L125
				1.31"[33.27mm] Dia. Clamp		L131
Knight RAD5300 [KKB I]	D		1.38"[35.05mm] Dia. Clamp	L138		
				1.44"[36.57mm] Dia. Clamp		L144
				1.50"[38.10mm] Dia. Clamp		L150
Knight RAD5500 [KKB IIL]	E		1.56"[39.62mm] Dia. Clamp	L156		
				1.63"[41.40mm] Dia. Clamp		L163
				1.69"[42.67mm] Dia. Clamp		L168
Knight RAD700 [KKB II]	F		1.75"[44.45mm] Dia. Clamp	L175		
				1.81"[45.97mm] Dia. Clamp		L181
				1.88"[47.75mm] Dia. Clamp		L188
				1.94"[49.27mm] Dia. Clamp		L194
				2.00"[50.8mm] Dia. Clamp		L200
I-Beam Trolley 3.25" or 3.33" Flange Flat Rail	G		2.13"[56.10mm] Dia. Clamp	L213		
				2.19"[55.63mm] Dia. Clamp		L219
				2.25"[57.15mm] Dia. Clamp		L225
				2.31"[58.67mm] Dia. Clamp		L231
I-Beam Trolley 2.66" Flange 4" S-Beam	H		2.38"[60.45mm] Dia. Clamp	L238		
				2.44"[61.98mm] Dia. Clamp		L244

### Note:

- Spring Balancer torque tubes are ideal in conditions where there is a need for the tool to return to the full UP position after fastening.
- Cylinder torque tubes are ideal in conditions where there is a need for the tool to remain in the same position after fastening. In other words, it remains balanced at any position in the vertical travel.
- \* Custom options available, please call a Knight Representative for further information.
- \*\* Safety Cable sold separately (#RWA4133).

"L" LENGTH	MODEL #
12.0" [304.8mm]	M12
24.0" [609.6mm]	M24
36.0" [914.4mm]	M36
48.0" [1219.2mm]	M48
"L" LENGTH	MODEL #
12.0" [304.8mm]	N12
24.0" [609.6mm]	N24
36.0" [914.4mm]	N36
48.0" [1219.2mm]	N48

